

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

export@sirsafety.com  
www.sirsafety.com

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: Flame Retardant Coverall</b>	<b>Code: 33271R</b>	<b>Flame Retardant</b>
---------------------------------------	---------------------	------------------------

### Description

Coverall in 100% Flame Retardant cotton fabric, weight 315 g/m<sup>2</sup>.  
Concealed metal zipper closure with Velcro, elastic cuffs, side pockets  
and chest pocket with flaps and Velcro, elastic waistband, ankle zipper  
closures.

- It features remarkable multi-protective properties and is able to  
guarantee a high level of comfort while maintaining softness, lightness  
and breathability



- The complete range can be produced in orange and red colours.

Suitable for protecting the operator from accidental contact with minor  
flames, molten metal splashes, low values of convective and radiant heat,  
and accidental electric contact up to 100 V of short duration.

The product is designed and manufactured according to the Directive  
89/686/EEC.

It is classified as PPE Cat.II.



Category <b>II</b>	Colours Red	Available Sizes 44-62
Quantity/Carton <b>50</b>	Important Information Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Metalworking Industry, Metallurgical Industry, Foundries, Plastic materials processing, Gas, water and electricity Industries, Firefighting Teams.
Dexterity	EC Standards EN 11611 CE  Class:1;A1 EN 11612 CE  Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E2 Contact Heat:F1	Storage and cleaning We recommend to follow the washing instructions. Resistance up to 25 washings. 