

EN 11612 CE

٢

Limited Flame Spread:A1

Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E2 Contact Heat:F1

TECHNICAL SHEET
-----------------

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL SYSTEM CEA; Sir Safety System S.p.A. Single-member company VAT Nr. IT 03359340548 export@sirsafety.com Wholly-owned subsidiary of Sir Holding Srl Viale Europa 74 www.sirsafety.com - 100 0001 -Via dei Fornaciai, 9 - Santa Maria degli Angeli 20090 Cusago Milano DNV.GI 06081 Assisi - Perugia - Italy Tel. +39 02.90394575 (R.A.) Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 Fax +39 02.90394441 1000 021 Name: Flame Retardant Jacket Code: 33273R Flame Retardant Description Jacket in 100% Flame Retardant cotton fabric, weight 315 g/m<sup>2</sup>. It features a chinese collar with Velcro to protect the neck. Concealed front zipper closure with flap and snap buttons; two side pockets and one chest pocket all with flaps and snap buttons, elastic cuffs. The jacket shall be worn in combination with the bib-trousers or trousers. - It features remarkable multi-protective properties and is able to guarantee a high level of comfort while maintaining softness, lightness and breathability. - The complete range can be produced in orange and red colours. Suitable for protecting the operator from accidental contact with minor flames, molten metal splashes, low values of convective and radiant heat, and accidental electric contact up to 100 V of short duration. The product is designed and manufactured according to the Directive 89/686/EEC. It is classified as PPE Cat.II. Category Colours **Available Sizes** 44-62 II Red Quantity/Carton Important Information Recommended for Keep in a cool dry place, far from heat sources Metalworking Industry, Metallurgical Industry, and direct light. Foundries, Plastic materials processing, Gas, water Make sure the garment is in good condition, and electricity Industries, Firefighting Teams. 50 undamaged and clean before use. Once you become aware of a damage, you should immediately replace it. Dexterity EC Standards Storage and cleaning EN 11611 CE We recommend to follow the washing instructions. Resistance up to 25 washings. Class:1;A1

