



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

 \bigcirc

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: Flame Retardant Bib-Trousers Code: 33276 Flame Retardant

Description

Bib-trousers in 100% Flame Retardant cotton fabric, weight 315 g/m². It features a concealed metal zipper closure, functional side pockets with flaps and Velcro, one back pocket on the right, rear elastic waistband and metal side buttons, elastic shoulder straps with metal buckles.

- It features remarkable multi-protective properties and is able to guarantee a high level of comfort while maintaining softness, lightness and breathability.
- The complete range can be produced in orange and red colours.

The bib-trousers shall be worn in combination with the jacket.

Suitable for protecting the operator from accidental contact with minor flames, molten metal splashes, low values of convective and radiant heat, and accidental electric contact up to 100 V of short duration.

Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E2 Contact Heat:F1

The product is designed and manufactured according to the Directive 89/686/EEC.

It is classified as PPE Cat.II.



it is classified as i i	L Gat.II.	
Category	Colours	Available Sizes
II	Green	44-62
Quantity/Carton	Important Information	Recommended for
20	Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Metalworking Industry, Metallurgical Industry, Foundries, Plastic materials processing, Gas, water and electricity Industries, Firefighting Teams.
Dexterity	EC Standards	Storage and cleaning
	EN 11611 CE	We recommend to follow the washing instructions. Resistance up to 25 washings.
	Class:1;A1	
	EN 11612 CE	5.4.50