

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: Flame Retardant Hood	Code: 33278	Flame Retardant
-----------------------------------	--------------------	------------------------

Description

Hood with shoulder-length cape, internally lined with flame retardant material; aluminised Kevlar inserts to protect the ears, adjustable front opening with Velcro and rear elastic.

- It features remarkable multi-protective properties and is able to guarantee a high level of comfort while maintaining softness, lightness and breathability.

The hood is suitable only for the protection of head and shoulders against hazards of short-term contact with flames, radiant and convective heat and in welding processes.

The product is designed and manufactured according to the Directive 89/686/EEC.

It is classified as PPE Cat.II.



Category II	Colours Green	Available Sizes Unica
-----------------------	------------------	--------------------------

Quantity/Carton 50	Important Information Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Metalworking Industry, Metallurgical Industry, Foundries, Plastic materials processing, Gas, water and electricity Industries, Firefighting Teams.
------------------------------	---	---

Dexterity	<p>EC Standards</p> <p>EN 11611 CE  Class:1;A1</p> <p>EN 11612 CE  Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E2 Contact Heat:F1</p>	<p>Storage and cleaning</p> <p>We recommend to follow the washing instructions. Resistance up to 25 washings.</p> 
-----------	---	--