

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: Polytech Color Trousers	Code: 35210NG	Polytech New Generation
--------------------------------------	----------------------	--------------------------------

Description

Trousers made of a technical fabric composed by 75% cotton, 24% polyester, 1% antistatic fibre fabric, weight 290 g/m². It features a fly with zip and button, two front welt pockets, rear pocket with flap and Velcro, two three-dimensional functional pockets with flaps and Velcro on the legs.

The trousers shall be worn with the jacket.

- The Polytech New Generation series is made with a multi-purpose fabric that combines antistatic properties with resistance to flames, heat and chemical products.

- Thanks to its features it is multi-purpose, practical and resistant, breathable and comfortable.







In combination with the trousers it is possible to wear our under garments: Carboflame undershirt art. 35285 and Carboflame underpants art. 35286, meeting the point A.2 of IEC 61482-2 which is stating that the electric arc protective clothing shall be used with under garments made of materials that would not melt with the arc.

The product is designed and manufactured to comply with the requirements of Directive 89/686/EEC.
It is classified as PPE Cat. III.



Category III	Colours Navy blue with grey inserts.	Available Sizes 44-62
------------------------	---	--------------------------

Quantity/Carton 50	Important Information Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Petrochemical Industry, Metalworking Industry, Refining Industry, Chemical Industry, Industrial Maintenance and Assemblies, Gas, Water and Electricity Mains Maintenance and Management, Oil & Gas industry.
------------------------------	---	---

Dexterity	<p>EC Standards</p> <p>EN 1149 CE</p>  <p>EN 11611 CE</p>  Class:1;A1 <p>EN 11612 CE</p>  Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E3 <p>CEI EN 61482</p>  Class:1 <p>EN 13034</p> 	<p>Storage and cleaning</p> <p>We recommend to follow the washing instructions. Wash separately from other types of garments to avoid the transfer of inflammable fibres.</p> 
-----------	--	--