



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: Light Carboflame Coverall Code: 35282B Light Carboflame and Carboflame

Description

Coverall with shirt collar in 99% cotton, 1% carbon fibre, 230 g/m². two-way central zipper closure with flap and Velcro, chest pockets with zipper and flaps with Velcro, loop for gas detector above right pocket; pocket on left sleeve with flap and Velcro, frontal slanted pockets with flaps and Velcro, hidden exterior-to-interior access, elastic waistband. Two back pockets with flaps and Velcro, knee pad pockets with Velcro closure; ruler pocket with flap and Velcro, reflective band on the shoulders, legs and arms, triple stitching.

- The Light Carboflame Coverall guarantees a high level of protection while maintaining lightness and breathability of the fabric.
- It is suitable for welding processes.
- Ensures great comfort, thanks to the percentage of cotton used.
- Night safety due to the reflective bands.

In combination with the coverall, is it possible to wear our under garments: Carboflame undershirt art. 35285 and Carboflame underpants art. 35286, meeting the point A.2 of IEC 61482-2 which is stating that the electric arc protective clothing shall be used with under garments made of materials that would not melt with the arc.

The product is designed and manufactured according to the Directive 89/686/EEC.

It is classified as PPE Cat.II.



Category	Colours	Available Sizes
II	Blue	XS-3XL
Quantity/Carton	Important Information	Recommended for
500	Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Petrochemical Industry, Oil & Gas Industries, Mining Industry.
Dexterity	EC Standards EN 1149 CE EN 11611 CE Class:1;A1 EN 11612 CE Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Contact Heat:F1	Storage and cleaning We recommend to follow the washing instructions.