

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

[export@sirsafety.com](mailto:export@sirsafety.com)  
[www.sirsafety.com](http://www.sirsafety.com)

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: V-Gard 500 Helmet</b>	<b>Code: 38312</b>	<b>Head Protection - MSA</b>
--------------------------------	--------------------	------------------------------

### Description

High quality helmet with ABS shell with Staz-On 4-point head harness and textile straps with ratchet wheel adjustment, for increased stability. Incorporated slots for hearing and face protection.  
Weight: 400 g.  
Size adjustment between 52-62 cm.

Approved EN 397 standard and responding to optional requirements:

- Very low temperature (-30°C)
- Lateral deformation (LD)
- Molten metal splashes (MM)
- Electrical insulation (440V AC)
- Electrical insulation approval: EN 50365 electric shock up to 1000 V AC or 1500 V DC
- Antistatic approval: EN 13463-1 for the zone 1,2,21 and 22, Group IIA.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 397, EN 50365, EN 13463. It is classified as PPE Cat. III.



Category <b>III</b>	Colours Red	Available Sizes 52-62
Quantity/Carton <b>20</b>	Important Information Make sure the helmet is in good condition before use and its shell is not damaged: inspect for cracking, abrasions, change of colouring or dents. Once you become aware of a damage, you should immediately replace it.	Recommended for Safety helmet suitable to protect the worker's head from objects falling from a height or accidental impacts in industrial plants. The ABS shell ensures a high impact and chemical resistance, thus making the helmet a perfect protection device in chemical and petrochemical industry.
Dexterity	EC Standards EN 397 CE  EN 13463-1 CE Values: 1, 2, 21, 22 Group: IIA  EN 50365	Storage and cleaning Keep in a cool dry place, far from heat sources and direct light. Clean using only a neutral detergent and warm water. Do not use any solvents.