

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciaci, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: Premium Respirator FFP2 NR D	Code: 45190	Premium Disposable Respirators
---	--------------------	---------------------------------------

Disposable Premium respirator suitable for medium toxicity environments up to 12 times the TLV.
Pack of 20 pieces.

- Latex-free elastic straps, do not cause skin allergies.
- While not in use, thanks to its shape, the respirator remains in upright position, avoiding the accumulations of polluting agents in the inner part in contact with the face.
- Better face adaptability, due to its concave shape.
- Completely metal-free to prevent rusting.
- Greater protection from fine and toxic dusts, due to its new filter surface which passed the D test. This test is performed with Dolomite dusts and certifies a higher level of protection with added anti-clogging properties.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 149.
It is classified as PPE Cat. III.

FFP2 NR D

FFP2: Nominal Protection Factor: 12

Operational Protection Factor: 10

NR: disposable

D: The respirator has passed the dolomite clogging test.



Category II	Colours White	Available Sizes Unica
Quantity/Carton 240	Important Information Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Protects against solid and liquid aerosols in concentrations up to 12 times the TLV. Suitable for metal sanding and grinding, cleaning and pest control with soapy water on incinerators, on cement production and urban traffic, demolition/cutting of plaster, wood and pottery, foundries and metal grinding.
Dexterity	EC Standards EN 149:2001 + A1:2009 CE FFP2 NR D	Storage and cleaning Keep in a cool dry place, far from heat sources.