

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel. +39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



**Name: Premium Respirator FFP2 NR D With
Exhalation Valve**

Code: 45191

Premium Disposable Respirators

Disposable Premium respirator with exhalation valve. Suitable for medium toxicity environments up to 12 times the TLV.
Pack of 10 pieces.

- Latex-free elastic straps, do not cause skin allergies.
- While not in use, thanks to its shape, the respirator remains in upright position, avoiding the accumulations of polluting agents in the inner part in contact with the face.
- Better face adaptability, due to its concave shape.
- Completely metal-free to prevent rusting.
- Greater protection from fine and toxic dusts, due to its new filter surface which passed the D test. This test is performed with Dolomite dusts and certifies a higher level of protection with added anti-clogging properties.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 149.
It is classified as PPE Cat. III.

FFP2 NR D

FFP2: Nominal Protection Factor: 12

Operational Protection Factor: 10

NR: disposable

D: The respirator has passed the dolomite clogging test.



| | | |
|-------------------------------|--|--|
| Category III | Colours White | Available Sizes Unica |
| Quantity/Carton 120 | Important Information Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it. | Recommended for Protects against solid and liquid aerosols in concentrations up to 12 times the TLV. Suitable for demolition and cutting of plaster, bricks and tiles, metal burring. |
| Dexterity | EC Standards EN 149:2001 + A1:2009 CE FFP2: ND: D: | Storage and cleaning Keep in a cool dry place, far from heat sources. |