

## **TECHNICAL SHEET**

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: FH2 Hood Code: 45346 Powered Air-Purifying Tornado System - Scott

## **Description**

Light, full hood covering head and shoulders. The sealing frame of the FH1 mask is in Neoprene and is manufactured from a durable PU-coated nylon material. The enhanced visor in flexible PETG grants a wider vision.

Minimum airflow: 140 l/m Assigned Protection Factor: 40 Nominal Protection Factor: 500 Actual hood weight: 190 g Noise Level: <75 dB (A)

Hood Material: Polyurethane coated Nylon

Hose Material: Polyurethane Visor Material: PETG Eye Protection: EN 166 1F

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 12941. It is classified as PPE Cat. II.



Category	Colours	Available Sizes
II	Grey	
Quantity/Carton	Important Information	Recommended for
1	The hood cannot be considered a chemical protective clothing. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	
Dexterity	EC Standards EN 12941 CE	Storage and cleaning Keep in a cool dry place, far from heat sources.