

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

**export@sirsafety.com**  
**www.sirsafety.com**

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



|                       |                    |   |
|-----------------------|--------------------|---|
| <b>Name: FH6 Hood</b> | <b>Code: 45353</b> | <b>Powered Air-Purifying Tornado System - Scott</b> |
|-----------------------|--------------------|---|

### Description

Incorporated with a helmet in accordance with EN 397, it combines head, face and respiratory protection in a single product. Hearing protection can also be attached if required.

Minimum airflow: 140 l/m  
Assigned Protection Factor: 20  
Nominal Protection Factor: 50  
Actual hood weight: 920 g  
Noise Level: <55 dB (A)  
Head Protection: EN 397, LD, MM, -30°, 440 V a.c.  
Helmet Material: Polyamide  
Hose Material: Polyurethane  
Visor Material: Polycarbonate  
Eye Protection: EN 166 1bt 3 9

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 12941.  
It is classified as PPE Cat. III.



|                             |   |  |
|-----------------------------|---|--|
| Category<br><b>III</b>      | Colours<br>White  | Available Sizes  |
| Quantity/Carton<br><b>1</b> | Important Information<br>The hood cannot be considered a chemical protective clothing. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it. | Recommended for  |
| Dexterity                   | EC Standards<br>EN 12941 CE   | Storage and cleaning<br>Keep in a cool dry place, far from heat sources. |