



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: FH21 Hood Code: 45358 Powered Air-Purifying Tornado System - Scott

Description

Full hood, lightweight and comfortable with head and shoulder protection. Completely antistatic. The sealing frame of the mask is in Neoprene to allow the highest level of protection without compromising the wearer's comfort.

Minimum airflow: 140 l/m Assigned Protection Factor: 40 Nominal Protection Factor: 500 Actual hood weight: 220 g Noise Level: <75 dB (A)

Hood Material: Antistatic Polyurethane coated Nylon

Hose Material: Polyurethane Visor Material: PETG Eye Protection: EN 166 1F

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 12941. It is classified as PPE Cat. III.



Category	Colours	Available Sizes
III	White	
Quantity/Carton	Important Information	Recommended for
1	The hood cannot be considered a chemical protective clothing. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	
Dexterity	EC Standards EN 12941 CE	Storage and cleaning Keep in a cool dry place, far from heat sources.
	LIN 12071 OL	Treep in a coor dry place, far from fleat sources.