

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

[export@sirsafety.com](mailto:export@sirsafety.com)  
[www.sirsafety.com](http://www.sirsafety.com)

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: Kit for Dust X-Plore 3500 in rubber + 2 filters Pure P3 R</b>	<b>Code: 45582</b>	<b>Half-Masks - Dräger</b>
--	--------------------	----------------------------

### Description

Twin filter half mask with bayonet connection made of innovative “DrägerFlex” material conceived for the Dräger X-Plore 3500 mask. “DrägerFlex” combines hypoallergenic properties with excellent chemical resistance and ensures an optimal fit even with eyeglasses. Provides a secure stable fit to the head thanks to its self-centering and adjustable retention system. Suitable for all needs. The mask features a head harness in soft plastic material with smooth edges and four elastic straps adjustable in length, to ensure a perfect fit to the face. Features quick-fit bayonet filter connection allowing for an even weight distribution and a wide field-of-vision. Total weight: approx. 95 g. The kit is provided with 2 filters Pure P3 R.



The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, perceived by DL 475/92, and to conform to the requirements of EN 140. It is classified as PPE Cat. III.

Category <b>III</b>	Colours	Available Sizes <b>S-L</b>
Quantity/Carton <b>1</b>	Important Information The half mask's maximum storage life is 6 years from date of manufacture. Should be stored in dry dust-free conditions, not liable to deformation.	Recommended for
Dexterity	EC Standards EN 140 CE  EN 143 CE	Storage and cleaning Cleaning the mask immediately after use will help prevent premature wear. Do not use any solvents such as acetone, alcohol, benzol, spirits, trichloroethylene, etc. Clean all its parts with a cloth, warm water and a neutral detergent, following carefully the washing instructions. Then rinse thoroughly under running water.