



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy

Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: Blue Power Corded Earplugs Code: 51917 Reusable Ear Plugs

Description

Corded ear plugs in special anallergic and washable compound. Pack of 200 pairs.

SNR 29 dB

Hertz frequency: H Attenuation = 27 Hertz frequency: M Attenuation = 27 Hertz frequency: L Attenuation = 26

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:63/31.6/ 5.6/26; Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:125/32.7/5.7/27; Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:250/30.9/5.9/25; Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:500/30.6/5.2/25.4; Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:1000/37.4/8.1/29.3; Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:2000/29.9/5.1/24.8; Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:4000/40.3/7.7/32.6; Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:8000/44.6/5.0/39.6;

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 352. It is classified as PPE Cat. II.



Category	Colours	Available Sizes
II	Red - Blue	Unica
Quantity/Carton	Important Information	Recommended for
10	Make sure the device is in good condition before use. Once you become aware of a damage, you should immediately replace it.	Suitable in noisy environments.
	Re-usable earplugs.	
Dexterity	EC Standards	Storage and cleaning
	EN 352 CE	Keep in a cool dry place, far from heat sources. Keep the earplugs clean, so they do not attract dust and dirt before use, promoting proper hygiene in the ear canal. Clean with a damp cloth. Do not use any solvents.