

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

[export@sirsafety.com](mailto:export@sirsafety.com)  
[www.sirsafety.com](http://www.sirsafety.com)

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: Grillon Hook Adjustable Lanyard 2 m</b>	<b>Code: 55234</b>	<b>Rope Access and Confined Space Kit - Petzl</b>
--	--------------------	---

### Description

The Grillon Hook adjustable lanyard is used to build work positioning systems as a complement to a fall-arrest system. Its length can be very easily and precisely adjusted as necessary, for comfortable positioning at the work station.

Used doubled on the harness lateral attachment points for an even weight distribution (user has weight on his feet): adjustment occurs when pressing the rotating cam. It can be used in single mode on the ventral attachment point to distribute the weight evenly between the waist belt and the leg straps (when suspended); adjustment occurs only moving the handle and holding the free end of the lanyard (it is necessary to open the device so as to remove the protective sheath). Removable protective sheath to protect the lanyard from the contact points, liable to damage it while enhancing its sliding features.

Weight: 625 g. Length: 2 m.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 358. It is classified as PPE Cat. III.



Category <b>III</b>	Colours	Available Sizes Unica
Quantity/Carton <b>1</b>	Important Information This device must not be used beyond its limitations or beyond its original purpose. Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for The device shall be used in combination with the other work-positioning devices in confined spaces and tree climbing.
Dexterity	EC Standards EN 358 CE	Storage and cleaning Keep in a cool dry place, far from UV radiation and chemicals. Clean and dry the item if necessary.