

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



| | | |
|-------------------------------|--------------------|--|
| Name: Vertex ST Helmet | Code: 55247 | Framing and Roofing Kit - Petzl |
|-------------------------------|--------------------|--|

Description

Comfortable helmet for industry, polycarbonate shell with high protection, meets the EN 397 standards and the optional requirements for electrical insulation, molten metal splashes, lateral deformation and use in low temperatures down to - 30°C.

Head circumference: 53-63 cm.

Weight: 455 g.

The helmet features:

- Side slots for mounting hearing protection.
- Possible application of protective face shield.
- Slot for mounting PIXA headlamp.
- Four positioning hooks for mounting a headlamp with an elastic band.
- Chinstrap designed to release in case of impact (breaking strength lower than 25 daN).

Weight: 455 g.

- Conforms to the EN 397 and EN 12492 standards for protection against impact.

- Meets the requirements of the EN 397 and EN 50365 standards for electrical insulation.

- Meets European standard EN 397 with approved extra requirements for lateral deformation, molten metal splash and low temperature (-30°C).

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 397 et EN 12492.

It is classified as PPE Cat. III.



| | | |
|------------------------------|---|---|
| Category III | Colours White, Red | Available Sizes Unica |
| Quantity/Cartron 1 | Important Information Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it. | Recommended for The device shall be used in combination with the other work-positioning devices in confined spaces. |
| Dexterity | EC Standards EN 397 CE EN 50365 EN 12492 CE | Storage and cleaning Keep in a cool dry place, far from heat sources. Clean the shell with warm soapy water, then rinse with clear water. Do not use any solvents. |