

SAFETY SYSTEM® WORKERS PROTECTOR		TECHNI	CAL SHEE	Т
Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686	VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441	export@sirsafety.com www.sirsafety.com	COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =	DNV-GL

Lanyards	ng Double Twisted Rope	Code: 55345	Energy Absorbers	
Description				
Double twisted 2 m rope lanyard, 12 mm wide, with energy absorber equipped with 1 Anapurna karabiner and 1 Montblanc karabiners. Weight: 1020 g.				
Minimum breaking streng Static strength: 15 kN su Lifetime of the device: 10		ing date.		
The energy absorber is made up of 44 mm wide webbing, fully folded and wrapped. In the event of a fall, the webbing inside the packing tears automatically therby reducing the impact forcetransmitted to the user to less than 6 Kn. Conforms to EN 355. Sir offers a wide range of energy absorbing webbings and lanyards, available in several lenghts and with different hooks provided at the ends.				
Category	Colours		Available Sizes	
	Green		Unica	
Quantity/Carton Ir	mportant Information		Recommended for	
1 N	Read carefully the user shee Make sure the item is in good Indamaged before use. Onc If a damage, you should imm	d condition, e you become aware	Ideal for vertical tasks in dangerous positions.	
Dexterity	C Standards		Storage and cleaning	
E	EN 355 CE		Keep in a dry place, far from heat sources.	